





The FortiVoice mid-enterprise IP PBX voice solutions give you total call control and sophisticated communication features for excellent customer service and efficient employee collaboration. Powerful, affordable and simple, FortiVoice mid-enterprise systems deliver powerful features and value to offices with up to 2000 phone users. FortiVoice phone systems include everything you need to handle calls professionally, control communication costs and stay connected everywhere.

Built-in fundamentals

FortiVoice mid-enterprise systems include all the fundamentals of enterprise-class voice communications, with no additional licenses to buy or cards to install. Auto attendants, auto provisioning, line/extension appearance, ring groups, user privileges, call queue, call barge, multilocation integration and much more are built-in. FortiVoice systems are easy to purchase, easy to install and easy to manage, so you save the headaches that come with most enterprise phone systems.

User appeal

Your people will like it too. The FortiVoice personal web portal lets your staff view their call logs, configure and manage their own messaging and access other features. Your employees get control over their phones, and your IT staff get a break from having to configure every little change.

Key Features & Benefits

Multiple line types	Support for PRI (T1/E1) digital lines, VoIP and traditional analog lines, depending on the model.
Multilocation networking	Integrates multiple locations, around the block or across the country with no long-distance charges.
Rich call features	Line/extension appearance, call queue, call barge, phone profile, ring group, call recording, rule-based dial plan, individual/group voicemail, and much more.
Flexibility	Multiple mode scheduling, flexible number management, re-assignable extensions, and caller ID modification.
Ease of configuration	Visual auto attendant config, built-in DHCP server, auto phone provisioning and web-based management and user web portal.
Comprehensive system monitoring	Real-time call status monitoring, call statistics, call logs, and call reports, and network traffic capture.

The network voice solution from the network security experts

- Built-in features, including auto attendants, music on hold, remote extensions and much more
- Web-based management and user interfaces
- Password policy enforcement
- · Real-time call status monitoring
- · Call recording
- Line/extension appearance
- · Call queue
- Call barge
- Auto provisioning
- · Rule-based dial plan

FORTIVOICE AWARDS











FEATURES

•	Automatic phone provisioning
•	Auto attendants
•	Individual and group voicemail
•	Remote extensions
•	External IP extensions
•	Dial-by-name directory
•	Voicemail
•	Voicemail to e-mail
•	Music on hold
•	Ring groups
•	Fax over IP/PRI/PSTN
•	Fax archive

•	Fax to e-mail
•	Send fax from user portal
•	LDAP authenticate
•	User privileges
•	Rule-based dial plan
•	Hot desking
•	Virtual number
•	Mode scheduling
•	Personal and system speed dial
•	Web-based management interface

Web-based user portal Web-based directory lookup

•	Web-based operator console
•	Personal blacklist
•	Line/extension appearance
•	Call recording and remote storage
•	802.1Q VLAN support
•	Network traffic capture
•	SIP over TLS
•	Password policy enforcement
•	Call conference/bridge
•	Call hold/transfer/park/pickup
•	Intercom
•	Call forward

 Paging to selected phones
Call queue
Call barge
Follow-me
 Real-time call status monitoring
Call detail record logging
Call report
Caller ID modification
Caller-based direct inward dialing
Multilocation networking
PRI and R2 signaling

· High availability

SPECIFICATIONS

	FORTIVOICE 200D	FORTIVOICE 200D-T	FORTIVOICE 2000E-T2
Hardware Specifications			
10/100/1000 Interfaces (RJ-45)	4	4	4
Traditional Telephone Lines (FXOs)	0	4	0
Primary Rate Interface (PRI)	0	1	2
Analog Extension (FXS)	0	1	0
Total Hard Drive Capacity	1X 1 TB	1X 1 TB	1X 1 TB
Hardware Form Factor	Rack Mount (1U)	Rack Mount (1U)	Rack Mount (1U)
Dimensions			
Height x Width x Length (in)	1.77 x 17.05 x 13.86	1.77 x 17.05 x 13.86	1.77 x 17.05 x 13.86
Height x Width x Length (mm)	45 x 433 352	45 x 433 352	45 x 433 352
Weight	15.4 lbs (6.98 kg)	16 lbs (7.26 kg)	16 lbs (7.26 kg)
Environment			
Power Required	100-240 V AC	100-240 V AC	100-240 V AC
Power Consumption (Avg.)	121 W	122.65 W	122.65 W
Heat Dissipation	205 BTU/h	210 BTU/h	210 BTU/h
Operating Temperature	32-104°F (0-40°C)	32-104°F (0-40°C)	32-104°F (0-40°C)
Storage Temperature	-31–158°F (-35–70°C)	-31–158°F (-35–70°C)	-31–158°F (-35–70°C
Humidity	5-95% non-condensing	5-95% non-condensing	5–95% non-condensino
Capacity			
VoIP trunks	100	100	100
IP extensions	2000	2000	2000
Remote extensions	100	100	100
Concurrent calls	200	200	200
Auto attendants	100	100	100
Conferences	20	20	20
Voicemail storage	900 GB	900 GB	900 GB
Codec support	G.711 µ-law/A-law,	G.729a, G.722, G.726	

FortiVoice mid-enterprise business phone systems are supported for use in the US, Canada, France, Germany, Italy, Spain, the UK, and more. For up-to-date availability information, visit www.fortivoice.com/availability.html.

ORDER INFORMATION

Product	SKU	Description
FortiVoice-200D	FVC-200D	FortiVoice-200D, 4x 10/100/1000 ports, 4 GB RAM, 1x 1 TB storage.
	FVC-200D-BDL-311-12	Hardware plus 1 year 8x5 FortiCare
	FC-10-T0200-311-02-DD	8x5 FortiCare Contract
	FC-10-T0200-247-02-DD	24x7 FortiCare Contract
FortiVoice-200D-T	FVC-200D-T	FortiVoice-200D-T, 4x 10/100/1000 ports, 4x FXO, 1x FXS, 1x PRI, 4 GB RAM, 1x 1 TB storage.
	FVC-200D-T-BDL-311-12	Hardware plus 1 year 8x5 FortiCare
	FC-10-T0201-311-02-DD	8x5 FortiCare Contract
	FC-10-T0201-247-02-DD	24x7 FortiCare Contract
FortiVoice-2000E-T2	FVC-2000E-T2	FortiVoice-2000E-T2, 4x 10/100/1000 ports, 2x PRI, 8 GB RAM, 1x 1 TB Storage, 2000 extensions, 100 VoIP trunks.
	FVC-2000E-T2-BDL-311-12 FC-10-T2000-311-02-DD	Hardware plus 1 year 8x5 FortiCare 8x5 FortiCare Contract
	FC-10-T2000-247-02-DD	24x7 FortiCare Contract
Related Products	SKU	Description
FortiVoice-VM	FVC-VM-BASE	Base license for stackable FortiVoice-VM (includes 50 extensions)
	FVC-VM-25	License to add 25 extensions to FortiVoice-VM (Maximum 300 in total)
	FC1-10-T00VM-248-02-12	1 Year FortiCare, 24x7 phone, OS updates: Renewals (1-50 extensions)
	FC2-10-T00VM-248-02-12	1 Year FortiCare, 24x7 phone, OS updates: Renewals (1-125 extensions)
	FC3-10-T00VM-248-02-12	1 Year FortiCare, 24x7 phone, OS updates: Renewals (1-250 extensions)



GLOBAL HEADQUARTERS

Fortinet Inc. 899 Kifer Road Sunnyvale, CA 94086 United States

Tel: +1.408.235.7700 Fax: +1.408.235.7737

EMEA SALES OFFICE

120 rue Albert Caquot 06560, Sophia Antipolis, France Tel: +33.4.8987.0510

Fax: +33.4.8987.0501

APAC SALES OFFICE

300 Beach Road #20-01 The Concourse Singapore 199555 Tel: +65.6513.3730 Fax: +65.6223.6784

Prol. Paseo de la Reforma 115 Int. 702 Col. Lomas de Santa Fe, C.P. 01219 Del. Alvaro Obregón México D.F. Tel: 011-52-(55) 5524-8480

LATIN AMERICA SALES OFFICE

Copyright© 2014 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.