

IPC322E-IR-F36(60) 1080P Fixed Dome IP Camera



Key Features

Optics

- Automatic day and night with removable IR-cut filter(ICR)
- Smart-IR technology for adaptive IR illumination, to enhance the image at night
- 30 m (98 ft) IR LED
- 3D noise reduction

Compression

- Dual streams to meet the different requirements for bandwidth and frame rate
- ROI (Region of Interest) to improve image quality of the key area for a low-bandwidth network
- Customized OSD to provide multiple fonts including crochet and outline fonts

Network

- NAA (Network Auto-Adaptability) technology to secure effective surveillance even with network packet loss
- UNP(Universal Network Passport) patented technology for NAT traversal
- Dual direct-to-iSCSI data block storage
- ONVIF Conformance


Structure

- Wide temperature range: -35°C to 60°C (-31°F to 140°F)
- IK10 vandal resistant
- IP66-rated


Specifications

Camera	IPC322E-IR-F36-IN	IPC322E-IR-F60-IN
Sensor	1/2.8", 2Megapixel, progressive scan CMOS	
Lens	3.6 mm, F1.8	6 mm, F1.8
Angle of View (H)	84.7°	53.2°
Day/Night	IR-cut filter with auto switch (ICR)	
Image Mirroring	Enable/Disable	
IR	Smart-IR ,30m (98 ft) IR range	
Video		
Maximum Resolution	1920 × 1080	
Video Compression	H.264	
Frame Rate	1080P (1920*1080) 30 fps; 720P (1280*720) 30 fps; D1 (720*576) 25 fps	
Video Streaming	Dual	
OSD	3 Groups of OSD: Time OSD, Name OSD(up to 8), customized OSD	
Privacy Mask	Up to 4 areas	
Audio		
Audio Compression	G.711	
Two-way Talking	Support	
Storage		
Back-end Storage	Dual direct-to-iSCSI data block storage	
Interface		
Audio I/O	3.5 mm audio interface	
	Input: impedance 35 kΩ; amplitude 2 V [p-p]	
	Output: impedance 600 Ω; amplitude 2 V [p-p]	
Alarm I/O	1 alarm inputs and 1 alarm output	
	Support for alarm-triggered actions	
Network	1 10M/100M Base-TX Ethernet	
Power Supply	12 V DC (DC connector)	
General		
Power	9 ~ 12 V DC, or PoE (IEEE802.3 af)	
	Power consumption: 3.5 W (IR 2 W)	
Dimensions (Ø x H)	Φ109 x 81 mm (Ø4.3" x 3.2")	
Weight	0.45 kg (1.0 lb)	
Operating Conditions	-35°C ~ +60°C (-31°F ~ 140°F), Humidity ≤ 90% RH(non-condensing)	
Vandal Resistant	IK10	
Ingress Protection	IP66	

Dimensions



Installation



Ceiling mount

Accessories

Installation mode	Accessories	Description
Ceiling mount	Mounting pedestal is included in the Product package	Ceiling

Zhejiang Uniview Technologies Co., Ltd.
South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P.R.China 310051
Email: overseasbusiness@uniview.com; globalsupport@uniview.com
<http://www.uniview.com>
©2013 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.